



# Sun Fire™ T1000 Server Site Planning Guide

---

Sun Microsystems, Inc.  
www.sun.com

Part No. 819-3749-11  
July 2006, Revision A

Submit comments about this document at: <http://www.sun.com/hwdocs/feedback>

Copyright 2006 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.sun.com/patents> and one or more additional patents or pending patent applications in the U.S. and in other countries.

This document and the product to which it pertains are distributed under licenses restricting their use, copying, distribution, and decompilation. No part of the product or of this document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any.

Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and in other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, Java, docs.sun.com, Sun Fire, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and in other countries.

All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and in other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

U.S. Government Rights—Commercial use. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

---

Copyright 2006 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, Californie 95054, Etats-Unis. Tous droits réservés.

Sun Microsystems, Inc. a les droits de propriété intellectuels relatants à la technologie qui est décrit dans ce document. En particulier, et sans la limitation, ces droits de propriété intellectuels peuvent inclure un ou plus des brevets américains énumérés à <http://www.sun.com/patents> et un ou les brevets plus supplémentaires ou les applications de brevet en attente dans les Etats-Unis et dans les autres pays.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a.

Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, Java, docs.sun.com, Sun Fire, et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays.

Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciées de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

LA DOCUMENTATION EST FOURNIE "EN L'ÉTAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFAÇON.



# Sun Fire T1000 Server Site Planning Guide

---

This guide provides the specifications and site requirements you need when planning the installation of the Sun Fire™ T1000 server.

For safety and compliance information, refer to the *Sun Fire T1000 Server Safety and Compliance Manual* and the *Important Safety Information for Sun Hardware Systems* document that came with your system.

This guide contains the following sections:

- [“Physical Dimensions” on page 1](#)
- [“Clearance for Service Access” on page 2](#)
- [“Environmental Specifications” on page 2](#)
- [“Power Source Requirements” on page 3](#)
- [“General Site Preparation Notes” on page 5](#)

---

## Physical Dimensions

These are the physical specifications for the Sun Fire T1000 server.

Description	U.S.	Metric
Width	16.8 in.	425 mm
Depth	19.0 in.	483 mm
Height	1.75 in., 1 rack unit	43 mm
Weight (without PCI card and rackmounts)	20 lb	9.1 kg
Weight (with slide rails)	24 lbs	10.9 kg

---

## Clearance for Service Access

These are the minimum clearances needed for service.

Description	Specification
Clearance, front of system	36 in (91 cm)
Clearance, rear of system	36 in (91 cm)

---

## Environmental Specifications

These are the environmental specifications for the Sun Fire T1000 server.

Description	Specification
Operating Temperature:	
• Sea level to 3000 ft (900m)	• 41°F to 95°F (5°C to 35°C)
• Above 3000 ft/900m	• Decrease maximum temperature as altitude increases, 1.6°F/1000 ft (1°C/300m)
Operating Humidity	10 to 90% noncondensing
Storage Temperature	-40 to 158°F, -40 to 70°C
Non-operating Humidity	93% RH noncondensing, 100°F (38°C) Max Wet Bulb
Operating Altitude	0 to 10,000 ft (3,000m)

---

# Power Source Requirements

The Sun Fire T1000 server has an autoranging power supply.

<b>Description</b>	<b>Specification</b>
Operating input voltage range	100 to 240 VAC, 50-60 Hz (Input voltage tolerance $\pm 10\%$ )
Maximum operating input current	2.2 A at 100 to 120 VAC 1.1 A at 200 to 240 VAC
Typical operating input power	180 W
Maximum operating input power	220 W
Typical heat dissipation	614 BTU/hr.
Maximum heat dissipation	750 BTU/hr.

---

# Agency Compliance Specifications

The Sun Fire T1000 server complies with the following specifications.

---

Category	Relevant Standards
Safety	UL/CSA-60950-1, EN60950-1, IEC60950-1 CB Scheme with all country deviations, IEC825-1, 2, CFR21 part 1040, CNS14336, GB4943
RFI/EMI	EN55022 Class A 47 CFR 15B Class A ICES-003 Class A VCCI Class A AS/NZ 3548 Class A CNS 13438 Class A KSC 5858 Class A GB9254 Class A EN61000-3-2 GB17625.1 EN61000-3-3
Immunity	EN55024 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-4-4 IEC 61000-4-5 IEC 61000-4-6 IEC 61000-4-8 IEC 61000-4-11
Telecommunications	EN300-386
Regulatory Markings	CE, FCC, ICES-003, C-tick, VCCI, GOST-R, BSMI, MIC, UL/cUL, UL/S-mark, CCC

---

---

# General Site Preparation Notes

Your environmental control system must provide intake air for the server which complies with the limits specified in [“Environmental Specifications” on page 2](#).

To avoid overheating, *do not* direct warmed air:

- Toward the front air intake of the server
- Toward the server access panels

---

**Note** – When you receive your server, place it in the environment in which you will install it. Leave in its shipping crate at its final destination for 24 hours. This resting period prevents thermal shock and condensation.

---

The server has been tested to meet all functional requirements when operating in the operating environmental limits presented in [“Environmental Specifications” on page 2](#). Operating computer equipment in extremes of temperature or humidity increases the failure rate of hardware components. To minimize the chance of component failure, use the server within the optimal temperature and humidity ranges.

## Ambient Temperature

An ambient temperature range of 69.8°F (21°C) to 73.4°F (23°C) is optimal for system reliability. At 71.6°F (22°C) it is easy to maintain safe relative humidity levels. Operating in this temperature range provides a buffer if the environmental support systems fail.

## Ambient Relative Humidity

Ambient relative humidity levels between 45% and 50% are the most suitable for data processing operations in order to:

- Prevent corrosion
- Provide an operating time buffer in the event of environmental control system failure
- Help avoid failures caused by the intermittent interference from static discharges that occur when relative humidity is too low

Electrostatic discharge (ESD) is easily generated and less easily dissipated in areas where the relative humidity is below 35%, and becomes critical when levels drop below 30%.

## Airflow Considerations

- Ensure unobstructed airflow through the chassis.
- Inlet air enters at the front of the server and exits from the back.
- Ventilation openings such as cabinet doors, for both the inlet and exhaust of the server should provide a minimum open area of 33.3 in.<sup>2</sup> (215 cm<sup>2</sup>) each. This equates to a 60% open area perforation pattern across the front and rear area of the server (17.5 in. x 3.2 in.; 445 mm x 81 mm). The impact of other open area characteristics that are more restrictive should be evaluated by the user.
- Front and rear clearance of the server should allow a minimum of 0.2 in. (5 mm) at the front of the system and 3.1 in. (80 mm) at the rear of the server when mounted. These clearance values are based on the inlet and exhaust impedance (available open area) and assume a uniform distribution of the open area across the inlet and exhaust areas. Clearance values greater than these might improve cooling performance.

---

**Note** – The combination of inlet and exhaust restrictions such as cabinet doors and the spacing of the server from the doors can affect the cooling performance of the server and should be evaluated by the user. The server placement is particularly important for high temperature NEBS environments where the server inlet ambient temperature is 131°F (55°C).

---

- Care should be taken to prevent recirculation of exhaust air within a rack or cabinet.
- Cables should be managed to minimize interfering with the server exhaust vent.
- Air temperature rise through the system is approximately 59°F (15°C).